

DATE OF COMPILATION: 01.06.2017

REVISION: 15.12.2022

VERSION NUMBER: 3.0

Safety data sheet in accordance with COMMISSION REGULATION (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. PRODUCT IDENTIFIER

Trade name: TOILET BLOCK TRI FORCE DYNAMIC LAVENDER

Designation: Toilet block on the basis of surface-active agents and fragrant component.

Contains: Benzenesulfonic acid, C10-13-alkyl derivs., sodium salts; Sulfonic acids, C14-16

(even numbered)-alkane hydroxy and C14-16 (even numbered)-alkene, sodium salts.

UFI: XD81-F1AF-V000-G3MS

1.2. RELEVANT IDENTIFIED USES OF THE SUBSTANCE OR MIXTURE AND USES ADVISED AGAINST

Identified uses: Product for cleaning and refreshing toilet bowls.

Uses advised against: any type of uses not mentioned above and in point 7.3.

1.3. DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEET:

Manufacturer: "Pol-Hun" M. BIELSKA Sp. J.

Address: 11 Listopada 65, 95-040 Koluszki, Poland

Telephone: +48 (44) 725 30 00

E-mail address for a person responsible for the SDS: polhun@polhun.pl

1.4. EMERGENCY TELEPHONE NUMBER

+48 (44) 725 30 19 (LABORATORY "**Pol-Hun" M. Bielska Sp. J.** (available during working days from 7^{00} a.m. up 20^{00} p.m.)

112- EMERGENCY TELEPHONE NUMBER

SECTION 2: HAZARDS IDENTIFICATION

2.1. CLASSIFICATION OF THE SUBSTANCE OR MIXTURE

The mixture is classified according to REGULATION (EC) No 1272/2008 as:

Eye Dam. 1 - Eye Damage of category 1 with hazard statement: H318 Causes serious eye damage.

Skin Irrit. 2 - Skin Irritation of category 2 with hazard statement: H315 Causes skin irritation.

Aquatic Chronic 3 - Hazardous to the aquatic environment – Chronic Hazard of category 3 with hazard statement:

str. 1/18

Trade name: TOILET BLOCK TRI FORCE DYNAMIC LAVENDER

Manufacturer: "Pol – Hun" M. Bielska Sp. j.

Address: 11-listopada 65, 95-040 Koluszki
Telephone/Fax +48(44) 725 30 00 / 725 30 01

H412 Harmful to aquatic life with long lasting effects.

2.2. LABEL ELEMENTS

Hazard pictogram:



Signal word: Danger

Hazard statements:

H318 Causes serious eye damage.

H315 Causes skin irritation.

H412 Harmful to aquatic life with long lasting effects.

Precautionary Statements:

P102 Keep out of reach of children.

P101 If medical advice is needed, have product container or label at hand.

P280 Wear protective gloves and eye protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P302+P352 IF ON SKIN: Wash with plenty of water.

P501 Dispose of contents/container to the person entitled to the disposal of waste

or stored in a place designated by the municipality.

Contains: Benzenesulfonic acid, C10-13-alkyl derivs., sodium salts; Sulfonic acids,

C14-16 (even numbered)-alkane hydroxy and C14-16 (even numbered)-alkane,

sodium salts.

EUH208 Contains: 3,7-dimethyloctan-3-ol. May produce an allergic reaction.

Detergent labeling according to Detergent Regulation 648/2004/EC:

Constituents: anionic surfactants >30%; non-ionic surfactants <5%; perfumes, Coumarin,

Limonene.

2.3. OTHER HAZARDS

The substances of the mixture do not meet the criteria for persistent, bioaccumulative and toxic (PBT) or very persistent and very bioaccumulative (vPvB) (at a concentration equal to or greater than 0,1 % by weight) in accordance with Annex XIII of (REACH) regulation.

The substances of the mixture are not included in the list established in accordance with Article 59(1) of (REACH) regulation for having endocrine disrupting properties (at a concentration equal to or greater than 0,1 % by weight).

The substances of the mixture are not identified as having endocrine disrupting properties (at a concentration equal to or greater than 0,1 % by weight) in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100(3) or Commission Regulation (EU) 2018/605(4).

Trade name: TOILET BLOCK TRI FORCE DYNAMIC LAVENDER

Manufacturer: "Pol – Hun" M. Bielska Sp. j.

Address: 11-listopada 65, 95-040 Koluszki
Telephone/Fax +48(44) 725 30 00 / 725 30 01

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. SUBSTANCES

not applicable.

3.2. MIXTURES

Hazard substances and substances for which there are Community workplace exposure limits:

Substance name	Concentr ation (% m/m)	Number CAS	Number WE	Number registration	Classification in accordance with Directive (WE) nr 1272/2008
Benzenesulfonic acid, C10- 13-alkyl derivs., sodium	15 - 25	68411-30-3	270-115-0	01-2119489428-22-0039	Acute Tox. 4; H302
salts					Eye Dam. 1; H318
					Skin Irrit. 2; H315
					Aquatic Chronic 3; H412
Sulfonic acids, C14-16	5 - 15	68439-57-6	270-407-8	01-2119513401-57-xxxx	Eye Dam. 1, H318
(even numbered)-alkane hydroxy and C14-16 (even numbered)-alkene, sodium salts			[931-534-0]		Skin Irrit. 2, H315
					Eye Irrit. 2; H319
Sodium carbonate	5 - 15	497-19-8	207-838-8	01-2119485498-19-xxxx	
Sulfuric acid, mono-C12- 18-alkyl esters, sodium	3 - < 10	68955-19-1	273-257-1	01-2119490225-39-xxxx	Skin Irrit. 2, H315
salts					Eye Dam. 1, H318
					Aquatic Chronic 3; H412
					Specific concentration limits: Eye Dam. 1, H318; C ≥ 20 % Eye Irrit.2, H319; 10 % ≤ C < 20 %
Alcohols, C12-15,	0,1 – 1,0	68131-39-5	500-195-7	_	Acute Tox. 4; H302
ethoxylated	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,				Eye Dam. 1; H318
					Aquatic Chronic 3; H412
Amidaa 040 40/ssaa	0.4 . 4.6	00000 77.0	202 424 2	04 0440400440 00	Skin Irrit. 2, H315
Amides, C12-18(even- numbered) and C18(unsatd.), N-	0,1 - < 1,0	90622-77-8	292-481-0	01-2119489413-33-xxxx	Eye Dam. 1, H318
hydroxyethyl			[931-338-5]		Aquatic Chronic. 2; H411
					Eye Irrit. 2; H319
Diphenyl ether ¹⁾ (ingredient of fragrance)	0,3 - 0,6	101-84-8	202-981-2	01-2119472545-33-xxxx	Aquatic Acute 1; H400
					M=1
					Aquatic Chronic 3; H412

Trade name: TOILET BLOCK TRI FORCE DYNAMIC LAVENDER

Manufacturer: "Pol – Hun" M. Bielska Sp. j.

Address: 11-listopada 65, 95-040 Koluszki
Telephone/Fax +48(44) 725 30 00 / 725 30 01

3,7-dimethyloctan-3-ol	0,03 - 0,15	78-69-3	201-133-9	01-2119454788-21-xxxx	Skin Irrit. 2; H315
(ingredient of fragrance)	, , ,	201.000	OT THE IS IT OF THE ARRA	Eye Irrit. 2; H319	
					Skin Sens. 1B; H317

Full texts of hazard statements is listed in section 16.

SECTION 4: FIRST AID MEASURES

4.1 <u>DESCRIPTION OF FIRST AID MEASURES</u>

Inhalation:

not an inhalation hazard under normal conditions of use; if necessary move to fresh air.

Eye:

- remove any contact lenses;
- flush with plenty of water for at least 10-15 minutes with the eyelids held wide open, avoid strong stream of water, which can cause cornea injury;
- do not use any medicines before getting medical attention;
- get medical attention immediately;

Skin:

- take off all contaminated clothing immediately;
- wash off with plenty of water;
- get medical advice if irritation persists.

Ingestion:

- rinse mouth with plenty of water;
- do not induce vomiting;
- if vomiting occurs, the head should be kept low so that the vomit does not enter the lungs (aspiration);
- seek medical advice immediately.

4.2. MOST IMPORTANT SYMPTOMS AND EFFECTS BOTH ACUTE AND DELAYED

- inhalation none; no adverse effect expected when used as directed.
- skin contact irritation, redness; no adverse effect expected when used as directed.
- eye contact serious eye damage, irritation, pain, watering, redness; no adverse effect expected when used as directed.
- ingestion irritant to mouth, throat and stomach; no adverse effect expected when used as directed.

4.3. INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED No data available.

SECTION 5. FIREFIGHTING MEASURES

5.1. EXTINGUISHING MEDIA

Suitable extinguishing media: extinguishing dry chemical powder, foam. Unsuitable extinguishing media: direct water jet.

5.2. SPECIAL HAZARDS ARISING FROM THE SUBSTANCE OR MIXTURE

Combustion products: sulphur oxides and carbon oxides.

5.3. ADVICE FOR FIREFIGHTERS

Wear full fire resistant protective clothing and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

SECTION 6: ACCIDENTAL RELEASE MEASURES

¹⁾ a substance with Union workplace exposure limits.

Trade name: TOILET BLOCK TRI FORCE DYNAMIC LAVENDER

Manufacturer: "Pol – Hun" M. Bielska Sp. j.

Address: 11-listopada 65, 95-040 Koluszki
Telephone/Fax +48(44) 725 30 00 / 725 30 01

6.1. PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES

For non-emergency personnel:

- avoid contact with skin and eyes;
- wear chemical protection gloves and suits;
- wear appropriate goggles.

For emergency responders:

Suitable fabric for personal protective clothing:

- appropriate: gloves nitrile rubber, neoprene, PVC, according to EN 374; suitability and durability of gloves is dependent on application, frequency, duration of contact, chemical resistance of glove material.
- not appropriate: no data.

6.2. ENVIRONMENTAL PRECAUTIONS

keep away from drains, surface- and ground-water and soil.

6.3. METHODS AND MATERIAL FOR CONTAINMENT AND CLEANING UP

- clean up spillage promptly;
- collect free product and transfer it to suitable tanks or containers for safe disposal;
- dispose of according to the local regulations.

6.4. REFERENCE TO OTHER SECTIONS

Information regarding safe handling – see section 7.

Information regarding personal protection – see section 8.

Information regarding disposal consideration - see section 13.

SECTION 7: HANDLING AND STORAGE

7.1. PRECAUTIONS FOR SAFE HANDLING

- handle in accordance with good manufacturing practices and personal hygiene;
- avoid contact with skin and eyes;
- wash hands after use;
- wash any exposed skin immediately after any chemical contact;
- do not eat, drink and smoke in work areas;
- remove contaminated clothing and protective equipment before entering eating areas;
- wear protective equipment.

7.2. CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES

- store in a cool (5°C -35°C), dry, well ventilated area;
- keep containers upright and tightly closed;
- keep away from food, oxidising substances, acids.

7.3. SPECIFIC END USE(S)

No data available.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. CONTROL PARAMETERS

The mixture does contain substances with the national occupational exposure limit values that correspond to Union occupational exposure limit values in accordance with Directive 98/24/EC, including any notations as referred to in Article 2(3) of Commission Decision 2014/113/EU;

Substance name and CAS number	OEL-TWA		STEL		Country, Publication
number	ррт	mg/m³	ррт	mg/ m³	
Titanium dioxide [13463-67-7]	-	10	-		[Poland]Regulation of the Minister of Family, Labour and Social Policy of 12 June 2018 (DZ.U. 2018 poz. 286

Trade name: TOILET BLOCK TRI FORCE DYNAMIC LAVENDER

Manufacturer: "Pol – Hun" M. Bielska Sp. j.

Address: 11-listopada 65, 95-040 Koluszki
Telephone/Fax +48(44) 725 30 00 / 725 30 01

Titanium dioxide [13463-67-7]	-	10	-	-	[Belgium]
Titanium dioxide [13463-67-7]	-	6 total dust	-	12 total dust	[Denmark]
Titanium dioxide [13463-67-7]	-	11 inhalable aerosol	-	-	[France]
Titanium dioxide [13463-67-7]	-	0,3 (1)(2)(3)	-	2,4 (1)(2)(3)(4)	[Germany]
Titanium dioxide [13463-67-7]	-	10 (1)	-	-	[Ireland]
		4 (2)			
Titanium dioxide [13463-67-7]	-	10	•	-	[Latvia]
Titanium dioxide [13463-67-7]	-	10	•	15 (1)	[Romania]
Titanium dioxide [13463-67-7]	-	10 Inhalable aerosol	-	-	[Spain]
Titanium dioxide [13463-67-7]	-	5 Inhalable aerosol	-	-	[Sweden]
Titanium dioxide [13463-67-7]	-	10 inhalable aerosol	-	-	[United Kingdom]
		4 respirable aerosol			

Remarks:

Germany: (1) Excluding ultrafine particles (2) Respirable fraction (3) Multiplied by the material density (4) 15 minutes average value.

Ireland: (1) Inhalable fraction (2) Respirable fraction.

Romania: (1) 15 minutes average value.

Source: Based on GESTIS International Limit values Database.

Substance name and CAS number	OEL-TWA		STEL		Country, Publication
number	ррт	mg/m³	ррт	mg/ m³	
Cellulose (pure) [9004-34-6]	-	10	-	-	[Belgium]
Cellulose (pure) [9004-34-6]	-	10 inhalable aerosol	-	-	[France]
Cellulose (pure) [9004-34-6]	-	10 (1) 4 (2)	-	20 (1) (3)	[Ireland]
Cellulose (pure) [9004-34-6]	-	2	-	-	[Latvia]

TOILET BLOCK TRI FORCE DYNAMIC LAVENDER Trade name:

"Pol – Hun" M. Bielska Sp. j. Manufacturer: 11-listopada 65, 95-040 Koluszki Address: +48(44) 725 30 00 / 725 30 01 Telephone/Fax

Cellulose (pure) [9004-34-6]	-	10 inhalable aerosol	-	-	[Spain]
Cellulose (pure) [9004-34-6]	-	10 inhalable aerosol	-	-	[United Kingdom]
		4 respirable aerosol			

Remarks:

Ireland: (1) Inhalable fraction (2) Respirable fraction (3) 15 minutes reference period. Source: Based on GESTIS International Limit values Database.

Substance name and CAS	OEL.	OEL-TWA		TEL	Country, Publication
number	ррт	mg/m³	ррт	mg/ m³	
Diphenyl ether [101-84-8]	1	7	2(1)	14(1)	[Austria]
Diphenyl ether [101-84-8]	1	7	2(1)	14(1)	[Belgium]
Diphenyl ether [101-84-8]	1	7	2	14	[Denmark]
Diphenyl ether [101-84-8]	1	7	2 (1)	14 (1)	[European Union]
Diphenyl ether [101-84-8]	1	7	2(1)	14(1)	[Finland]
Diphenyl ether [101-84-8]	1	7	2(1)	14(1)	[France]
Diphenyl ether [101-84-8]	1(1)	7,1(1)	1(1)(2)	7,1(1)(2)	[Germany (AGS)]
Diphenyl ether [101-84-8]	1(1)	7,1(1)	1(1)(2)	7,1(1)(2)	[Germany (DFG)]
Diphenyl ether [101-84-8]	1	7	-	-	[Ireland]
Diphenyl ether [101-84-8]	1	7	2(1)	14(1)	[Latvia]
Diphenyl ether [101-84-8]	-	7	-	14	[Poland]
Diphenyl ether [101-84-8]	0,7	5	1,4(1)	10 (1)	[Romania]
Diphenyl ether [101-84-8]	1	7,1	2	14,2	[Spain]

Trade name: TOILET BLOCK TRI FORCE DYNAMIC LAVENDER

Manufacturer: "Pol – Hun" M. Bielska Sp. j.

Address: 11-listopada 65, 95-040 Koluszki
Telephone/Fax +48(44) 725 30 00 / 725 30 01

Diphenyl ether [101-84-8]	1	7	2(1)	14(1)	[Sweden]
Diphenyl ether [101-84-8]	1	7	2(1)	14(1)	[United Kingdom]

Remarks:

Austria (1) 15 minutes average value

Belgium (1) 15 minutes average value

European Union (1) 15 minutes average value Bold-type: Indicative Occupational Exposure Limit Value

Finland (1) 15 minutes average value

France: Indicative statutory limit values (1) 15 minutes average value

Germany (AGS) (1) Inhalable aerosol and vapour (2) 15 minutes reference period

Germany (DFG) (1) Inhalable fraction and vapour (2) 15 minutes reference period

Latvia (1) 15 minutes average value

People's Republic of China (1) 15 minutes average value

Romania (1) 15 minutes average value

Sweden (1) 15 minutes average value

United Kingdom (1) 15 minutes average value

Source: Based on GESTIS International Limit values Database.

Substance name and CAS number	OEL-	EL-TWA S		EL	Country, Publication
number	ррт	mg/m³	ррт	mg/ m³	
D-Limonene [5989-27-5]	25	140	50	280	[Finland]
D-Limonene [5989-27-5]	5	28	20	110	[Germany (AGS)]
D-Limonene [5989-27-5]	25	140	-	-	[Norway]
D-Limonene [5989-27-5]	30	168	-	-	[Spain]
D-Limonene [5989-27-5]	7	40	14	80	[Switzerland]

The mixture does not contain substances with the national occupational exposure limit values that correspond to Union limit values in accordance with Directive 2004/37/EC, including any notations as referred to in Article 2(3) of Decision 2014/113/EU;

The mixture does not contain substances with the national biological limit values that correspond to Union biological limit values in accordance with Directive 98/24/EC, including any notations as referred to in Article 2(3) of Decision 2014/113/EU;

<u>DNEL (Derived No Effect Level)</u> VALUES <u>determined for Benzenesulfonic acid, C10-13-alkyl derivs., sodium salts</u> <u>CAS No [68411-30-3] (all values are in mg/kg 100% product):</u>

Exposure time	Group	Route of	Value
		exposure	
Long-term (repeated)	Worker	dermal	170 mg/kg bw/day
Long-term (repeated)	Worker	inhalation	12 mg/m ³
Long-term	Consumer	oral	0,85 mg/kg bw/day

Trade name: TOILET BLOCK TRI FORCE DYNAMIC LAVENDER

Manufacturer: "Pol – Hun" M. Bielska Sp. j.

Address: 11-listopada 65, 95-040 Koluszki
Telephone/Fax +48(44) 725 30 00 / 725 30 01

(repeated)				
Long-term (repeated)	Consumer	dermal	85 mg/kg bw/day	
Long-term (repeated)	Consumer	inhalation	3 mg/m ³	

DNEL (Derived No Effect Level) Values determined for Sodium Carbonate CAS No [497-19-8]:

Exposure time	Population	Route of	Value
		exposure	
Long-term	Workers	inhalation	10 mg/m ³

<u>DNEL (Derived No Effect Level)</u> <u>Values determined for Sulfuric acid, mono-C12-18-alkyl esters, sodium salts CAS No [68955-19-1]:</u>

Exposure time	Group	Route of exposure	Value
Long-term repeated	Worker	dermal	4060 mg/kg bw/day
Long-term repeated	Worker	inhalation	285 mg/m ³
Long-term repeated	Consumer	oral	24 mg/kg bw/day
Long-term repeated	Consumer	dermal	2440 mg/kg bw/day
Long-term repeated	Consumer	inhalation	85 mg/m ³

DNEL (Derived No Effect Level) Values determined for Sulfonic acids, C14-16 (even numbered)-alkane hydroxy and C14-16 (even numbered)-alkane, sodium salts CAS No [68439-57-6]:

Exposure time	Group	Route of exposure	Value
Long-term systemic	Worker	dermal	2158.33 mg/kg bw/day
Long-term	Worker	inhalation	152.22 mg/m³
Long-term	Consumer	oral	12.95 mg/kg bw/day
Long-term	Consumer	dermal	1295 mg/kg bw/day
Long-term	Consumer	inhalation	45,04 mg/ m ³

<u>DNEL (Derived No Effect Level) Values determined for Amides, C12-18(even-numbered) and C18(unsatd.), N-hydroxyethyl No CAS [90622-77-8]:</u>

Exposure time	Group	Route of exposure	Value	
Long-term systemic	Worker	dermal	4,16 mg/kg bw/day	
Long-term systemic	Worker	inhalation	73,4 mg/m ³	
Long-term systemic	Consumer	oral	6,25 mg/kg bw/day	
Long-term systemic	Consumer	dermal	2,5 mg/kg bw/day	
Long-term systemic	Consumer	inhalation	21,73 mg/m3	

Trade name: TOILET BLOCK TRI FORCE DYNAMIC LAVENDER

Manufacturer: "Pol – Hun" M. Bielska Sp. j.

Address: 11-listopada 65, 95-040 Koluszki
Telephone/Fax +48(44) 725 30 00 / 725 30 01

DNEL (Derived No Effect Level) Values determined for Titanium Dioxide No CAS [13463-67-7]:

Exposure time	Group	Route of exposure	Value
Long-term, systemic	Worker	inhalation	10 mg/m ³
Long-term, systemic	Consumer	oral	700 mg/kg bw/day

<u>PNEC Values</u> (*Predicted No Effect Concentration*) for Benzenesulfonic acid, C10-13-alkyl derivs., sodium salts CAS No [68411-30-3]:

Route of exposure	Value
Water	0,268 mg/L
Sewage treatment plant STP	3,43 mg/L
Marine Water	0,0268 mg/L
Sediment (Fresh Water)	8,1 mg/kg

PNEC Values (*Predicted No Effect Concentration*) for Sulfonic acids, C14-16 (even numbered)-alkane hydroxy and C14-16 (even numbered)-alkane, sodium salts CAS No [68439-57-6]:

Route of exposure	Value
Fresh Water	0,024mg/L
Sewage treatment plant STP	4 mg/L
Marine Water	0,0024 mg/L
Sediment (Fresh Water)	0,767 mg/kg
Sediment (Marine Water)	0,0767 mg/kg
Soil	1,21 mg/kg

PNEC Values (Predicted No Effect Concentration) for Sulfuric acid, mono-C12-18-alkyl esters, sodium salts CAS No [68955-19-1]:

Route of exposure	Value
Water	0,098 mg/L
Sewage treatment plant STP	1084 mg/L
Marine Water	0,0098 mg/L
Sediment	3,45 mg/kg
Sediment (Marine)	0,345 mg/kg
Soil	0,631 mg/kg

PNEC Values (*Predicted No Effect Concentration*) for Amides, C12-18(even-numbered) and C18(unsatd.), N-hydroxyethyl No CAS [90622-77-8]:

Route of exposure	Value
Fresh Water	0,007mg/L
Sewage treatment plant STP	830 mg/L
Marine Water	0,0007 mg/L
Sediment (fresh water)	1,201 mg/kg
Sediment (marine water)	0,120 mg/kg
Soil	0,2354 mg/kg

PNEC Values (Predicted No Effect Concentration) for Titanium Dioxide No CAS [13463-67-7]:

Route of exposure	Value
-------------------	-------

Trade name: **TOILET BLOCK TRI FORCE DYNAMIC LAVENDER**

Manufacturer: "Pol - Hun" M. Bielska Sp. j. Address: 11-listopada 65, 95-040 Koluszki Telephone/Fax +48(44) 725 30 00 / 725 30 01

Fresh Water	0,127mg/L
Sewage treatment plant STP	100 mg/L
Marine Water	1 mg/L
Sediment (fresh water)	1000 mg/kg
Sediment (marine water)	100 mg/kg
Soil	100 mg/kg

8.2. EXPOSURE CONTROLS

Personal protective equipment:

Respiratory protection:

is not required during normal operations in a workplace.

Eye protection:

use protective tight-fitting goggles if eye exposure is reasonably probable.

Hand protection:

in case of long contact with product use suitable protective gloves

(suitable materials: neoprene, nitrile rubber, polyethylene or PVC- thickness 0,12mm;

breakthrough time > 2hours) according to EN 374.

Skin protection: use protective clothing against chemicals.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES

Physical state solid

Colour: white and dark violet Odour: characteristic. lavender

not determined for mixture; 198,5°C for Benzenesulfonic acid, C10-Melting point/freezing point:

13- alkyl derivs., sodium salts CAS No [68411-30-3]:

Boiling point or initial boiling point

and boiling range:

not determined

Flammability: the mixture is ignitable

Lower and upper explosion limit: does not apply Flash point: does not apply Auto-ignition temperature: does not apply Decomposition temperature: does not apply

white part: 10 -11 (1% water solution)

dark violet part: 8,5 - 10,5 (1% water solution)

Kinematic viscosity: does not apply

Solubility: soluble in water; 250 g/l for Benzenesulfonic acid, C10-13-alkyl

derivs., sodium salts CAS No [68411-30-3]

Partition coefficient: n-octanol/water

(log value): does not apply

Vapour pressure: not determined for mixture; 3*10-13 Pa (25°C) for Benzenesulfonic

acid, C10-13-alkyl derivs., sodium salts CAS No [68411-30-3]

Density and/or relative density: not determined Relative vapour density: does not apply Particle characteristics: not determined

9.2. OTHER INFORMATION

No data available.

SECTION 10: STABILITY AND REACTIVITY

10.1. **REACTIVITY**

The reactivity hazards of mixture has not been tested.

10.2 **CHEMICAL STABILITY**

Product is stable under recommended conditions of storage.

10.3. POSSIBILITY OF HAZARDOUS REACTIONS

Trade name: **TOILET BLOCK TRI FORCE DYNAMIC LAVENDER**

Manufacturer: "Pol – Hun" M. Bielska Sp. j. 11-listopada 65, 95-040 Koluszki Address: +48(44) 725 30 00 / 725 30 01 Telephone/Fax

None under normal conditions.

CONDITIONS TO AVOID

Keep away from humidity, high temperatures; keep away from source of heat and source of fire.

10.5. **INCOMPATIBLE MATERIALS**

Strong mineral acids.

10.6. **HAZARDOUS DECOMPOSITION PRODUCTS**

Sulphur oxides.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. INFORMATION ON HAZARD CLASSES DEFINED IN REGULATION (EC) No 1272/2008 Acute toxicity:

The mixture has not been tested. Based on the available data of the ingredients the classification criteria are not met.

ATE mix (oral) ~ 4000 mg/kg. (calculated according point 3.1.3.6.1. Annex I of Regulation CLP 1272/2008).

Acute toxicity of Benzenesulfonic acid, C10-13-alkyl derivs., sodium salts CAS No [68411-30-3]:

1080 mg/kg (rat); LD50 (oral): LD50 (dermal): >2000 mg/kg (rat). Acute toxicity of Sodium carbonate CAS No [497-19-8]:

LD50 (oral): 2800mg/kg (rat); LD50 (dermal): > 2000mg/kg; LC50 (inhalation): 2300mg/m³/2h (rat).

Acute toxicity of Sulfonic acids, C14-16 (even numbered)-alkane hydroxy and C14-16 (even numbered)-alkene, sodium salts CAS No [68439-57-6]:

2079 mg/kg (rat); LD50 (oral):

6300-13500mg/kg (rabbit); LD50 (dermal): LC50 (inhalation): >52 mg/l/4hours (rat).

Acute toxicity of Amides, C12-18(even-numbered) and C18(unsatd.), N-hydroxyethyl No CAS [90622-77-8]:

LD50 (oral): >5000 mg/kg (rat). LD50 (dermal): >2000 mg/kg (rabbit).

Acute toxicity of Sulfuric acid, mono-C12-18-alkyl esters, sodium salts CAS No [68955-19-1]:

LD50 (oral): ~ 2600 mg/kg (rat).

Acute toxicity of Alcohols, C12-15, ethoxylated CAS No [68131-39-5]:

LD50 (oral): 1700mg/kg (rat);

Skin corrosion/irritation:

The mixture has not been tested. Based on the available data of the ingredients the mixture is classified as - Causes skin irritation.

Irritant effect of Benzenesulfonic acid, C10-13-alkyl derivs., sodium salts CAS No [68411-30-3]:

Causes skin irritation. (test OECD 404, rabbit).

Ilrritant effect of Sulfonic acids, C14-16 (even numbered)-alkane hydroxy and C14-16 (even numbered)-alkene, sodium salts CAS No [68439-57-6]:

Test OECD 404 Acute Dermal Irritation/Corrosion - rabbit- Causes skin irritation.

Irritant effect of Amides, C12-18(even-numbered) and C18(unsatd.), N-hydroxyethyl No CAS [90622-77-8]:

Causes skin irritation.

Irritant effect of Sulfuric acid, mono-C12-18-alkyl esters, sodium salts CAS No [68955-19-1]:

Causes skin irritation.

Serious eye damage/eye irritation:

The mixture has not been tested. Based on the available data of the ingredients the mixture is classified as - Causes serious eye damage.

Irritant effect of Benzenesulfonic acid, C10-13-alkyl derivs., sodium salts CAS No[68411-30-3]:

Causes serious eye damage (test OECD 405, rabbit).

Irritant effect of Sulfonic acids, C14-16 (even numbered)-alkane hydroxy and C14-16 (even numbered)-alkene, sodium salts CAS No [68439-57-6]:

Test OECD 405 Acute Eye Irritation (rabbit) – causes eye damage.

Irritant effect of Amides, C12-18(even-numbered) and C18(unsatd.), N-hydroxyethyl No CAS [90622-77-8]:

Causes serious eve damage.

Irritant effect of Sulfuric acid, mono-C12-18-alkyl esters, sodium salts CAS No [68955-19-1]:

Causes serious eye irritation.

Trade name: TOILET BLOCK TRI FORCE DYNAMIC LAVENDER

Manufacturer: "Pol – Hun" M. Bielska Sp. j.

Address: 11-listopada 65, 95-040 Koluszki
Telephone/Fax +48(44) 725 30 00 / 725 30 01

Irritant effect of Sodium carbonate CAS No [497-19-8]:

Causes serious eye irritation.

Irritant effect of Alcohols, C12-15, ethoxylated CAS No [68131-39-5]:

Causes serious eye damage

Respiratory or skin sensitization:

The mixture has not been tested. Based on the available data of the ingredients the classification criteria are not met, but the mixture contains: **3,7-dimethyloctan-3-ol**; may produce an allergic reaction.

Skin sensitization of Benzenesulfonic acid, C10-13-alkyl derivs., sodium salts CAS No[68411-30-3]:

Not classified (test OECD 406, guinea pig).

Sensitization effect of Sulfonic acids, C14-16 (even numbered)-alkane hydroxy and C14-16 (even numbered)-alkene, sodium salts CAS No [68439-57-6]:

Test OECD 406 skin sensitization (dermal, guinea pig), result - has no sensitization properties.

Sensitization effect of Amides, C12-18(even-numbered) and C18(unsatd.), N-hydroxyethyl No CAS [90622-77-8]:

Not classified.

Sensitization effect of Sulfuric acid, mono-C12-18-alkyl esters, sodium salts CAS No [68955-19-1]:

Not classified.

Germ cell mutagenicity:

The mixture has not been tested. Based on the available data of the ingredients the classification criteria are not met.

Mutagenicity effect of Benzenesulfonic acid, C10-13-alkyl derivs., sodium salts CAS No [68411-30-3]:

Test OECD 471 Bacterial Reverse Mutation test – result: negative.

Test OECD 476 In vitro Mammalian Cell Gene Mutation test – result: negative.

Test OECD 473 In vitro Mammalian Chromosomal Aberration test – result: negative.

Mutagenicity effect of Sulfonic acids, C14-16 (even numbered)-alkane hydroxy and C14-16 (even numbered)-alkene, sodium salts CAS No [68439-57-6]:

Test OECD 471 Bacterial Reverse Mutation Test, result- negative;

Test OECD 476 In vitro Mammalian Cell Gene Mutation Test, result- negative;

Test OECD 473 In vitro Mammalian Chromosomal Aberration Test, result- negative.

Mutagenicity effect of Amides, C12-18(even-numbered) and C18(unsatd.), N-hydroxyethyl No CAS [90622-77-8]:

Ames test – result – negative.

Mutagenicity effect of Sulfuric acid, mono-C12-18-alkyl esters, sodium salts CAS No [68955-19-1]:

Not classified.

Mutagenicity effect of Sodium carbonate CAS No [497-19-8]:

Not classified.

Carcinogenicity:

The mixture has not been tested. Based on the available data of the ingredients the classification criteria are not met.

Carcinogenicity of Benzenesulfonic acid, C10-13-alkyl derivs., sodium salts No CAS [68411-30-3]:

No known significant effects or critical hazards.

Carcinogenicity of Sulfonic acids, C14-16 (even numbered)-alkane hydroxy and C14-16 (even numbered)-alkene, sodium salts CAS No [68439-57-6]:

Test – rat – exposure time: 2 years (oral), result- negative.

Test – mouse - exposure time: 92 weeks (3 days in week, dermal), result- negative.

Carcinogenicity of Amides, C12-18(even-numbered) and C18(unsatd.), N-hydroxyethyl No CAS [90622-77-8]:

Not classified.

Carcinogenicity of Sulfuric acid, mono-C12-18-alkyl esters, sodium salts CAS No [68955-19-1]:

Not classified.

Carcinogenicity of Sodium carbonate CAS No [497-19-8]:

Not classified.

Reproductive toxicity:

The mixture has not been tested. Based on the available data of the ingredients the classification criteria are not met.

Reproductive toxicity of Benzenesulfonic acid, C10-13-alkyl derivs., sodium salts CAS No [68411-30-3]:

Test OECD 416 Two-Generation Reproduction Toxicity Study (rat) - oral: NOAEL: 350 mg/kg bw/day.

Reproductive toxicity of Sulfonic acids, C14-16 (even numbered)-alkane hydroxy and C14-16 (even numbered)-alkene, sodium salts CAS No[68439-57-6]:

Test OECD 414 Prenatal Developmental Toxicity Study, rabbit, result: 2 mg/kg NOAEL.

Trade name: TOILET BLOCK TRI FORCE DYNAMIC LAVENDER

Manufacturer: "Pol – Hun" M. Bielska Sp. j.

Address: 11-listopada 65, 95-040 Koluszki
Telephone/Fax +48(44) 725 30 00 / 725 30 01

Reproductive toxicity of Sulfuric acid, mono-C12-18-alkyl esters, sodium salts CAS No [68955-19-1]:

Not classified.

Reproductive toxicity of Sodium carbonate CAS No [497-19-8]:

Not classified.

STOT - single exposure:

The mixture has not been tested. Based on the available data of the ingredients the classification criteria are not met.

STOT - repeated exposure:

The mixture has not been tested. Based on the available data of the ingredients the classification criteria are not met.

Aspiration hazard:

Not applicable, the mixture is solid.

Routes of exposure

The mixture has not been tested – no available data.

Symptoms related to the physical, chemical and toxicological characteristics:

inhalation - none;

skin contact - irritation, redness and pain of skin;

eye contact - serious damage to eyes; irritation, pain, watering, redness;

ingestion - irritant to mouth, throat and stomach, may cause nausea, vomiting.

Delayed and immediate effects as well as chronic effects from short and long-term exposure:

No available data.

Interactive effects:

No available data.

11.2. INFORMATION ON OTHER HAZARDS

Endocrine disrupting properties

The substances of the mixture are not identified as having endocrine disrupting properties for human health (at a concentration equal to or greater than 0,1 % by weight) in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100(3) or Commission Regulation (EU) 2018/605(4).

Other information

No data.

SECTION 12: ECOLOGICAL INFORMATION

12.1. TOXICITY

The mixture has not been tested. Based on the available data of the ingredients the mixture is classified as - Harmful to aquatic life with long lasting effects.

Toxicity of Benzenesulfonic acid, C10-13-alkyl derivs., sodium salts CAS No [68411-30-3]:

Fish - LC50: 1-5 mg/L/96h;

Algae- EC50: 29 mg/L/96h;

Daphnia - EC50: 1-5 mg/L/48h.

Long term study: NOEC (Fish, 28-196 days): 0,23 – 3,2 mg/L Long term study: NOEC (Algae, 15-28 days): 3,1 – 4,0 mg/L.

Long term study: NOEC (Daphnia, 2-32 days): 0,59 – 4,5mg/L.

Acute toxicity of Sulfonic acids, C14-16 (even numbered)-alkane hydroxy and C14-16 (even numbered)-alkane, sodium salts CAS No [68439-57-6]:

Test ISO 10253:2006 - Marine algal growth inhibition test with Skeletonema costatum and Phaeodactylum tricornutum EC50: 5,2mg/L/72 hours.

Test OECD 202 Daphnia sp. Acute Immobilisation Test, EC50: 4,53 mg/L/48hours.

Test OECD 209 Activated Sludge, Respiration Inhibition Test, IC50: 230 mg/L/3 hours, bacteria.

Test OECD 203 Fish, Acute Toxicity Test, LC50: 4,2 mg/L/96 hours.

Acute toxicity of Sodium carbonate CAS No [497-19-8]:

Trade name: TOILET BLOCK TRI FORCE DYNAMIC LAVENDER

Manufacturer: "Pol – Hun" M. Bielska Sp. j.

Address: 11-listopada 65, 95-040 Koluszki
Telephone/Fax +48(44) 725 30 00 / 725 30 01

Fish - LC50: 300mg/l/96h (Lepomis macrochirus;

Daphnia – LC50: 200-227 mg/l/48h.

Acute toxicity of Amides, C12-18(even-numbered) and C18(unsatd.), N-hydroxyethyl No CAS [90622-77-8]:

Fish – LC50: 10-100 mg/L – method ISO 7346/2 (semistatic).

Daphnia - EC50: 10-100 mg/L - method OECD 202.

Algae- EC50: 1-10 mg/L - method: OECD 201/DIN 38412.

Bacteria - EC0: >100mg/L - method OECD 209.

Acute toxicity of Sulfuric acid, mono-C12-18-alkyl esters, sodium salts CAS No [68955-19-1]:

Fish – **LC50:** 17 mg/L/96h.- (*Cyprinus carpio*). Daphnia – EC50: 15mg/L/48h (*Daphnia magna*).

Algae - ERC50: >20mg/L/72h.

Acute toxicity of Alcohols, C12-15, ethoxylated CAS No [68131-39-5]:

Fish - LC50: 1-10 mg/l/96h

12.2. PERSISTENCE AND DEGRADABILITY

The mixture has not been tested - no available data.

Persistence and degradability of Benzenesulfonic acid, C10-13-alkyl derivs., sodium salts CAS No [68411-30-3]:

Biodegradation: >99%, (OECD Screening test 301D and 303A);

Biodegradation: readily biodegradable in the OECD 301B CO₂ Evolution test: 85% biodegradability in 29 days.

Ready Biodegradability:>70% (OECD 301D);

Ready Biodegradability: >60% Oxygen uptake (OECD 301F);

Inherent test: 95-98% (OECD 302 A, B); Simulation test: 80-95% (OECD 303A).

Persistence and degradability of Sulfonic acids, C14-16 (even numbered)-alkane hydroxy and C14-16 (even numbered)-alkane, sodium salts CAS No [68439-57-6]:

Readily biodegradable.

Persistence and degradability of Amides, C12-18(even-numbered) and C18(unsatd.), N-hydroxyethyl No CAS [90622-77-8]:

Readily biodegradable.

Persistence and degradability of Sulfuric acid, mono-C12-18-alkyl esters, sodium salts CAS No [68955-19-1]:

Readily biodegradable > 93% (28 days).

Persistence and degradability of Sodium carbonate CAS No [497-19-8]:

Substance is inorganic and disassociate in water.

Persistence and degradability of Alcohols, C12-15, ethoxylated CAS No [68131-39-5]:

Test OECD 301D - 71,3% (28 dni).

12.3. BIOACCUMULATIVE POTENTIAL

The mixture has not been tested - no available data.

Bioaccumulative potential of Benzenesulfonic acid, C10-13-alkyl derivs., sodium salts CAS No [68411-30-3]:

BCF: 2-1000. It is not bioaccumulative.

Bioaccumulative potential of Sulfonic acids, C14-16-alkane hydroxy and C14-16-alkene, sodium salts CAS No [68439-57-6]:

LogPow: -1,3; BCF: 70,8;

It has low potential to accumulate.

Bioaccumulative potential of Sulfuric acid, mono-C12-18-alkyl esters, sodium salts CAS No [68955-19-1]:

BCF: -2,1 (OECD 107).

Bioaccumulative potential of Alcohols, C12-15, ethoxylated CAS No [68131-39-5]:

BCF-237

logPow: 2,03-6,24

12.4. MOBILITY IN SOIL

The mixture has not been tested - no available data.

12.5. RESULTS OF PBT AND vPvB ASSESSMENT

The mixture has not been tested - no available data.

The components of mixture are not PBT and vPvB.

12.6 ENDOCRINE DISRUPTING PROPERTIES

The substances of the mixture are not identified as having endocrine disrupting properties for the environment

Trade name: TOILET BLOCK TRI FORCE DYNAMIC LAVENDER

Manufacturer: "Pol – Hun" M. Bielska Sp. j.

Address: 11-listopada 65, 95-040 Koluszki
Telephone/Fax +48(44) 725 30 00 / 725 30 01

(at a concentration equal to or greater than 0,1 % by weight) in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100(3) or Commission Regulation (EU) 2018/605(4).

12.7. OTHER ADVERSE EFFECTS

The mixture has not been tested - no available data.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. WASTE TREATMENT METHODS

- dispose of according to local, state or national legislation;
- avoid disposing into drainage systems and into the environment;
- contaminated packaging dispose in the same way as the product itself.
- non-contaminated packages may be recycled

SECTION 14: TRANSPORT INFORMATION

ADR/RID/ADN/IMDG/IATA:

- 14.1. UN number or ID number: not applicable.
- 14.2. <u>UN proper shipping name:</u> not applicable.
- 14.3. TRANSPORT HAZARD CLASS(ES): not applicable.
- 14.4. PACKING GROUP: not applicable.

14.5. ENVIRONMENTAL HAZARDS:

The mixture has not been tested - no available data.

14.6. SPECIAL PRECAUTIONS FOR USER

See sections 6 to 8 of this Safety Data Sheet.

14.7. MARITIME TRANSPORT IN BULK ACCORDING TO IMO INSTRUMENTS

Not applicable

SECTION 15: REGULATORY INFORMATION

The mixture is not subject to Regulation (EC) No 1005/2009 of the European Parliament and of the Council of 16 September 2009 on substances that deplete the ozone layer, Regulation (EC) No 850/2004 of the European Parliament and of the Council of 29 April 2004 on persistent organic pollutants and amending Directive 79/117/EEC or Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals

15.1 <u>SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS/LEGISLATION SPECIFIC FOR THE SUBSTANCE OR MIXTURE</u>

REGULATION (EC) No 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

REACH (Article 59) - Candidate List of Substances of Very High Concern for Authorization - not applicable.

REACH (Annex XVII) – Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles - not applicable.

REACH (Annex XVII) – Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles - not applicable.

REACH (Annex XIV) - List of substances subject to authorization.- not applicable.

REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.

COMMISSION REGULATION (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

Trade name: TOILET BLOCK TRI FORCE DYNAMIC LAVENDER

Manufacturer: "Pol – Hun" M. Bielska Sp. j.

Address: 11-listopada 65, 95-040 Koluszki
Telephone/Fax +48(44) 725 30 00 / 725 30 01

Regulation (EC) No 648/2004 of the European Parliament and of the Council of 31 March 2004 on detergents.

Council Directive 98/24/EC of 7 April 1998 on the protection of the health an ad safety of workers from the risks related to

chemical agents at work.

Commission Directive 2000/39/EC of 8 June 2000 establishing a first list of indicative occupational exposure limit values in implementation of Council Directive 98/24/EC on the protection of the health and safety of workers from the risks related to

chemical agents at work.

Commission Directive 2006/15/EC of 7 February 2006 establishing a second list of indicative occupational exposure limit values in implementation of Council Directive 98/24/EC and amending Directives 91/322/EEC and 2000/39/EC.

Commission Directive 2009/161/EU of 17 December 2009 establishing a third list of indicative occupational exposure limit values in implementation of Council Directive 98/24/EC and amending Commission directive 2000/39/EC.

COMMISSION DIRECTIVE (EU) 2017/164 of 31 January 2017 establishing a fourth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC, and amending Commission Directives 91/322/EEC, 2000/39/EC and 2009/161/EU

Directive 2004/37/EC of the European Parliament and of the Council of 29 April 2004 on the protection of workers from the risks related to exposure to carcinogens or mutagens at work .

15.2. CHEMICAL SAFETY ASSESSMENT

The chemical safety assessment has not been carried out for the mixture.

SECTION 16: OTHER INFORMATION

The changes: section 1, 2, 3, 9, 11, 12, 14, 15, 16.

The classification of the mixture is based on:

- the category "acute toxicity" an additive method;
- the category "skin corrosion/irritation" an additive method;
- the category "serious eye damage/eye irritation" an additive method;
- the category "respiratory or skin sensitization" contents of sensitizing ingredients;
- the category "mutagenicity"- contents of classified ingredients;
- the category "carcinogenicity" contents of classified ingredients;
- the category "reproductive toxicity" contents of classified ingredients;
- the category "STOT repeated exposure" contents of classified ingredients;
- the category "STOT single exposure" contents of classified ingredients;
- the category "aspiration hazard" an additive method;
- the category 'ecotoxicological properties" an additive method.

Abbreviations and acronyms used in the safety data sheet:

PBT - Persistent, Bioaccumulative, Toxic;

vPvB - Very Persistent and very Bioaccumulative;

LD50 - Lethal Dose, 50%;

LC50 - Lethal Concentration 50%:

EC50 - half maximal effective concentration;

IC50 - half maximal inhibitory concentration;

OECD - Organization for Economic Cooperation and Development;

NOAEL - No Observed Adverse Effect Level;

NOEC - No Observed Effect Concentration;

BCF - bioconcentration factor.

logPow - octanol - water partition coefficient;

Koc - soil/water partition coefficient;

OEL - Occupational Exposure Limit;

TWA - Eight - hour Time Weighted Average;

STEL - Short Term Exposure Limit.

ADR – European Agreement concerning the International Carriage of Dangerous Goods by Road.

RID - Regulations concerning the International Carriage of Dangerous Goods by Rail (RID).

ADN – European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways.

IMDG – International Maritime Dangerous Goods Code.

IATA – International Air Transport Association.

<u>List of hazard statements and precautionary statements which are not written out in full under Sections 2 to 15:</u>

Acute Tox. 4 Acute toxicity of category 4.

Trade name:	TOILET BLOCK TRI FORCE DYNAMIC LAVENDER

Manufacturer: "Pol – Hun" M. Bielska Sp. j.

Address: 11-listopada 65, 95-040 Koluszki
Telephone/Fax +48(44) 725 30 00 / 725 30 01

Eye Dam. 1 Eye Damage of category 1.

Eye Irrit. 2 Eye Irritation of category 2.

Skin Irrit. 2 Skin Irritation of category 2.

Skin Sens. 1B Skin Sensitization of category 1B.

Aquatic Acute 1 Hazardous to the aquatic environment - Acute Hazard of category 1.

Aquatic Chronic 1 Hazardous to the aquatic environment - Chronic Hazard of category 1.

Aquatic Chronic 2 Hazardous to the aquatic environment - Chronic Hazard of category 2.

Aquatic Chronic 3 Hazardous to the aquatic environment - Chronic Hazard of category 3.

H302 Harmful if swallowed.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.

The information corresponds to the present state of our knowledge and is intended as a general description of our products and their possible applications. This document is neither a quality description of the product nor a guarantee of particular properties. The information are to be treated as aid to safety in transport, storage and usage of the product. This does not free the user from the responsibility of improper usage of the information above and also of improper compliance with the law norms in the field. Due to possible changes in our products and applicable national and international regulations and laws, the status of our products could change.